

HP Latex 365 Printer

Maximize your versatility with this full-feature, 1.63-m (64-in) HP Latex printer



Water-based HP Latex Technology is unique, delivering a combination of true application versatility, high image quality and high productivity, and a sustainable approach that's better for your operators, your business, and the environment.¹

Expand your applications—beat client expectations

- Print on traditional signage substrates and beyond—up to 1.63 m (64 in)—print textiles with the ink collector²
- Reach new indoor spaces that solvent can't. like healthcare—water-based HP Latex Ink prints are odorless
- Enjoy efficient, automated double-sided banner printing
- Produce sharp, consistent, repeatable image quality with high-efficiency curing, 6 colors, and 1200 dpi

Same day delivery—for highly demanding turnarounds

- High quality at high speeds—31 m² (334 ft²)/hr high-speed outdoor quality with HP OMAS, HP Latex Optimizer3
- Reach production speeds and avoid wait time—prints come out completely dry and ready to finish and deliver
- Gain productivity—reduce time between jobs with continuous printing
- You can minimize damage risk—scratch resistance is comparable to hard-solvent inks on SAV and PVC banner⁴

Keep your running costs low—boost your capacity

- Increase production time and reduce time monitoring the printer—automatic, reliable, low-maintenance printing
- Save time—HP Custom Substrate Profiling and i1 embedded spectrophotometer make ICC profiling automatic⁵
- Maintain high image quality over the life of the printer with user-replaceable HP Thermal Inkjet printheads
- Monitor your printer remotely with the free HP Latex Mobile app⁶

For more information, please visit hp.com/go/Latex365

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at

hp.com/communities/LKC

- Based on a comparison of HP Latex Ink technology to competitors with leading market share as of December, 2013 and analysis of published MSDS/SDSs and/or internal evaluation. Performance of specific attributes may vary by competitor and
- ink technology/formulation.

 Performance may vary depending on media—for more information, see <a href="https://personalization.gov/media-global-to-state-and-to-
 - Banner-quality prints in outdoor (4-pass 4-color) mode.
- Estimates by HP Image Permanence Lab on a range of media. Scratch-resistance comparison based on testing HP Latex Inks and representative hard-solvent inks. Outdoor display permanence tested according to SAE J2S27 using HP Latex Inks on a range of media, including HP media; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Laminated display permanence using HP Clear Gloss Cast Overlaminate. Results may vary based on specific media performance.

 5 ICC profiling with the spectrophotometer does not support uncoated textiles and backlits.
- 6 HP Latex Mobile is compatible with Android™ 4.1.2 or later and iOS 7 or later, and requires the printer and the smart phone or tablet to be connected to the Internet.

HP Latex 365 Printer (1.63 m / 64 in)

HP Latex Optimizer

- Achieve high image quality at high productivity
- Interacts with HP Latex Inks to rapidly immobilize pigments on the surface of the print

End-to-end sustainability—a better approach

HP Latex Technology delivers all the certifications that matter to your operators, your business, and the environment.7





Using water-based inks eliminates exposure to inks with hazard warning labels and high solvent concentrations, and simplifies ventilation, storage, and transportation requirements.

HP Latex Inks enable more differentiation—odorless prints go where solvent can't.



UL GREENGUARD GOLD¹⁰

HP is designing end-to-end sustainability into large-format printing. The HP Latex 365 Printer is EPEAT Bronze registered—a designation for reduced environmental impact.11







HP Latex Inks

- Scratch resistance comparable to hard-solvent inks on SAV and PVC banner—you can consider unlaminated use for short-term signage¹²
- Outdoor durability up to 5 years laminated, 3 years unlaminated13

HP Latex printheads

- · See fine details and smooth transitions with HP 831 Latex Printheads providing 1200 dpi native
- Keep day-one image quality by replacing the printheads yourself in a few minutes, without a service call



High-efficiency curing

• Prints are completely cured and dry inside the printer, and ready for immediate finishing and delivery



Easy maintenance and operation

• Accessible print zone with large window and lights

HP Optical Media Advance Sensor (OMAS) • Precise and accurate motion control of media

• Controls registration automatically including double-sided prints with automated registration

advance between print swaths

across sides14


• Enjoy low-maintenance printing with automatic drop detection and nozzle replacement



- Based on a comparison of HP Latex Ink technology to competitors with leading market share as of December, 2013 and analysis of published MSDS/SDSs and/or internal evaluation. Performance of specific attributes may vary by competitor and ink technology/formulation.
- Applicable to HP Latex Inks. UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see ul.com/EL). HP 831 Latex Ink Cartridges, certification number 14142007, certified by the Eco Mark Office of Japan Environment Association.
- Applicable to HP Latex Inks. UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg
- or greenguard.org.

 EPEAT registered where applicable/supported. See epeat.net for registration status by country.
- $Scratch-resistance\ comparison\ based\ on\ testing\ third-generation\ HP\ Latex\ lnks\ and\ representative\ hard-solvent\ inks.\ Estimates\ by\ HP\ Image\ Permanence\ Lab\ on\ a\ range\ of\ media.$
- HP image permanence estimates by HP Image Permanence Lab. Outdoor display permanence tested according to SAE J2527 on a range of media, including HP media; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Laminated display permanence using HP Clear Gloss Cast Overlaminate, GBC clear gloss 1.7 mil hot laminate, or Neschen Solvoprint Performance Clear 80 laminate. Results may vary based on specific media performance.
- For best results use media options intended for double-sided printing.
- ICC profiling with the spectrophotometer does not support uncoated textiles and backlits.
- The color variation inside a printed job has been measured at 10-pass mode on vinyl media within this limit: maximum color difference (95% of colors) <= 2 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant DS0, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 2 dE2000. Backlit substrates measured in transmission mode may yield different results.
- Performance may vary depending on media—for more information, see hp.com/go/mediasolutionslocator. For best results, use textiles that do not stretch. The ink collector is required for porous textiles.





HP Custom Substrate Profiling

- Simplified color management, directly from the front panel, 8-inch touchscreen
- Pre-installed generic and HP substrate profile library
- Create custom ICC profiles with the i1 embedded spectrophotometer¹⁵



Spectrophotometer

- Color consistency for balanced production
- i1 embedded spectrophotomer enables automatic calibration¹⁵
- Delivers consistent colors to <= 2 dE2000¹⁶
- Color emulation workflow





Ink collector

- Expand into textile signage, no need to trim off margins
- Print on a wide variety of textiles—including porous textiles—with the ink collector¹⁷



NEW

Easy, remote online operator training

 Online self-help learning tools—from the basics on how to start operating the printer to tips such as how to grow your business with new applications
 Visit: hp.com/communities/HPLatex300



HP Latex Technology

NEW

HP Quick Solutions App

- Perform actions to optimize image quality
- Direct access from the front panel

Technical specifications

Printing	Printing modes	91 m²/hr (980 ft²/hr) - Max Speed (1 pass)
		31 m²/hr (334 ft²/hr) - Outdoor High Speed (4 pass)
		23 m²/hr (248 ft²/hr) - Outdoor Plus (6 pass)
		17 m²/hr (183 ft²/hr) - Indoor Quality (8 pass)
		14 m²/hr (151 ft²/hr) - Indoor High Quality (10 pass)
		6 m²/hr (65 ft²/hr) - Backlits, Textiles, and Canvas (16 pass)
		5 m²/hr (54 ft²/hr) - High Saturation Textiles (20 pass)
	Print resolution	Up to 1200 x 1200 dpi
	Margins	$5\times5\times0\times0$ mm (0.2 \times 0.2 \times 0 \times 0 in) (without edge holders
	Ink types	HP Latex Inks
	Ink cartridges	Black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer
	Cartridge size	775 ml
	Printheads	6 (2 cyan/black, 2 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer)
	Color consistency ¹⁸	Average <= 1 dE2000, 95% of colors <= 2 dE2000
Media	Handling	Roll feed; take-up reel; automatic cutter (for vinyl, paperbased media, backlit polyester film)
	Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall-coverings, canvas, synthetics, mesh, textiles
	Roll size	254 to 1625-mm (10 to 64-in) rolls (580 to 1625-mm (23 to 64-in) rolls with full support)
	Roll weight	42 kg (92.6 lb)
	Roll diameter	250 mm (9.8 in)
		U= t= 0 F (10 7:1)
	Thickness	Up to 0.5 mm (19.7 mil)
Applications	Banners, Display Exterior signage,	op to 0.5 mm (19.7 mil) s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, per, Murals, POP/POS, Posters, Textile, Traffic signage,
	Banners, Display Exterior signage, Light boxes – pap Vehicle graphics	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film,
Connectivity Dimensions	Banners, Display Exterior signage, Light boxes – pap Vehicle graphics Interfaces	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, Der, Murals, POP/POS, Posters, Textile, Traffic signage,
Connectivity Dimensions	Banners, Display Exterior signage, Light boxes – pap Vehicle graphics Interfaces (standard)	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, per, Murals, POP/POS, Posters, Textile, Traffic signage, Gigabit Ethernet (1000Base-T)
Connectivity Dimensions	Banners, Display Exterior signage, Light boxes – pap Vehicle graphics Interfaces (standard) Printer	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, ber, Murals, POP/POS, Posters, Textile, Traffic signage, Gigabit Ethernet (1000Base-T) 2561 x 840 x 1380 mm (101 x 33 x 54 in)
Connectivity Dimensions (w x d x h)	Banners, Display Exterior signage, Light boxes – par Vehicle graphics Interfaces (standard) Printer Shipping	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, per, Murals, POP/POS, Posters, Textile, Traffic signage, Gigabit Ethernet (1000Base-T) 2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1250 mm (110.1 x 30 x 49.3 in)
Connectivity Dimensions (w x d x h)	Banners, Display Exterior signage, Light boxes – pap Vehicle graphics Interfaces (standard) Printer Shipping Operating area	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, per, Murals, POP/POS, Posters, Textile, Traffic signage, Gigabit Ethernet (1000Base-T) 2561 × 840 × 1380 mm (101 × 33 × 54 in) 2795 × 760 × 1250 mm (110.1 × 30 × 49.3 in) 2761 × 1840 mm (109 × 72 in)
Connectivity Dimensions (w x d x h) Weight What's in the	Banners, Display Exterior signage, Light boxes – par Vehicle graphics Interfaces (standard) Printer Shipping Operating area Printer Shipping HP Latex 365 Printer output platen protension kit, loading	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, per, Murals, POP/POS, Posters, Textile, Traffic signage, Gigabit Ethernet (1000Base-T) 2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1250 mm (110.1 x 30 x 49.3 in) 2761 x 1840 mm (109 x 72 in) 216 kg (476 lb)
Connectivity Dimensions (w x d x h) Weight What's in the box Environmen-	Banners, Display Exterior signage, Light boxes – pap Vehicle graphics Interfaces (standard) Printer Shipping Operating area Printer Shipping HP Latex 365 Printer tension kit, loading reference guide,	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, per, Murals, POP/POS, Posters, Textile, Traffic signage, Gigabit Ethernet (1000Base-T) 2561 × 840 × 1380 mm (101 × 33 × 54 in) 2795 × 760 × 1250 mm (110.1 × 30 × 49.3 in) 2761 × 1840 mm (109 × 72 in) 216 kg (476 lb) 303.5 kg (671.5 lb) nter, printheads, maintenance cartridge, ink collector, otector, printer stand, spindle, take-up reel, variable fronting accessory, user maintenance kit, edge holders, quick
Connectivity Dimensions (w x d x h) Weight What's in the box Environmen-	Banners, Display Exterior signage, Light boxes – pap Vehicle graphics Interfaces (standard) Printer Shipping Operating area Printer Shipping HP Latex 365 Printer output platen protension kit, loadir reference guide,	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, ber, Murals, POP/POS, Posters, Textile, Traffic signage, Gigabit Ethernet (1000Base-T) 2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1250 mm (110.1 x 30 x 49.3 in) 2761 x 1840 mm (109 x 72 in) 216 kg (476 lb) 303.5 kg (671.5 lb) hter, printheads, maintenance cartridge, ink collector, otector, printer stand, spindle, take-up reel, variable fronting accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords
Connectivity Dimensions (w x d x h) Weight What's in the box Environmental ranges	Banners, Display Exterior signage, Light boxes – par Vehicle graphics Interfaces (standard) Printer Shipping Operating area Printer Shipping HP Latex 365 Prin output platen protension kit, loadii reference guide, Operating temperature Operating humidity Sound pressure	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, per, Murals, POP/POS, Posters, Textile, Traffic signage, Gigabit Ethernet (1000Base-T) 2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1250 mm (110.1 x 30 x 49.3 in) 2761 x 1840 mm (109 x 72 in) 216 kg (476 lb) 303.5 kg (671.5 lb) There, printheads, maintenance cartridge, ink collector, printer stand, spindle, take-up reel, variable fronting accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) 55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep)
Connectivity Dimensions (w x d x h) Weight What's in the box Environmental ranges	Banners, Display Exterior signage, Light boxes – par Vehicle graphics Interfaces (standard) Printer Shipping Operating area Printer Shipping HP Latex 365 Prin output platen protension kit, loadii reference guide, operating temperature Operating humidity	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, per, Murals, POP/POS, Posters, Textile, Traffic signage, Gigabit Ethernet (1000Base-T) 2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1250 mm (110.1 x 30 x 49.3 in) 2761 x 1840 mm (109 x 72 in) 216 kg (476 lb) 303.5 kg (671.5 lb) Ther, printheads, maintenance cartridge, ink collector, printer stand, spindle, take-up reel, variable fronting accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) 55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep) 7.4 B(A) (printing); 5.7 B(A) (ready); < 3.5 B(A) (sleep)
Connectivity Dimensions (w x d x h) Weight What's in the box Environmental ranges	Banners, Display Exterior signage, Light boxes – par Vehicle graphics Interfaces (standard) Printer Shipping Operating area Printer Shipping HP Latex 365 Prin output platen protension kit, loadii reference guide, Operating temperature Operating humidity Sound pressure	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, per, Murals, POP/POS, Posters, Textile, Traffic signage, Gigabit Ethernet (1000Base–T) 2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1250 mm (110.1 x 30 x 49.3 in) 2761 x 1840 mm (109 x 72 in) 216 kg (476 lb) 303.5 kg (671.5 lb) There, printheads, maintenance cartridge, ink collector, printer stand, spindle, take-up reel, variable fronting accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) 55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep) 7.4 B(A) (printing); 85 watts (ready); < 2.5 watts (sleep)
Connectivity Dimensions (w x d x h) Weight What's in the box Environmental ranges	Banners, Display Exterior signage, Light boxes – pap Vehicle graphics Interfaces (standard) Printer Shipping Operating area Printer Shipping HP Latex 365 Printer output platen protension kit, loading reference guide, operating temperature Operating humidity Sound pressure Sound power	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, per, Murals, POP/POS, Posters, Textile, Traffic signage, Gigabit Ethernet (1000Base-T) 2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1250 mm (110.1 x 30 x 49.3 in) 2761 x 1840 mm (109 x 72 in) 216 kg (476 lb) 303.5 kg (671.5 lb) Ther, printheads, maintenance cartridge, ink collector, printer stand, spindle, take-up reel, variable fronting accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) 55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep) 7.4 B(A) (printing); 5.7 B(A) (ready); < 3.5 B(A) (sleep)
Connectivity Dimensions (w x d x h) Weight What's in the box Environmental ranges Acoustic	Banners, Display Exterior signage, Light boxes – pap Vehicle graphics Interfaces (standard) Printer Shipping Operating area Printer Shipping HP Latex 365 Printer output platen prottension kit, loadir reference guide,: Operating temperature Operating humidity Sound pressure Sound power Consumption	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, per, Murals, POP/POS, Posters, Textile, Traffic signage, Gigabit Ethernet (1000Base-T) 2561 × 840 × 1380 mm (101 × 33 × 54 in) 2795 × 760 × 1250 mm (110.1 × 30 × 49.3 in) 2761 × 1840 mm (109 × 72 in) 216 kg (476 lb) 303.5 kg (671.5 lb) hter, printheads, maintenance cartridge, ink collector, prector, printer stand, spindle, take-up reel, variable front ng accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) 55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep) 7.4 B(A) (printing); 85 watts (ready); < 2.5 watts (sleep) Input voltage (auto ranging) 200 to 240 VAC (-10% +10%) two wires and PE; 50/60 Hz (+/- 3 Hz); two power cords;
Connectivity Dimensions (w x d x h) Weight What's in the box Environmental ranges Acoustic	Banners, Display Exterior signage, Light boxes – pap Vehicle graphics Interfaces (standard) Printer Shipping Operating area Printer Shipping HP Latex 365 Printer output platen protension kit, loadir reference guide, Operating temperature Operating humidity Sound pressure Sound power Consumption Requirements	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, per, Murals, POP/POS, Posters, Textile, Traffic signage, Gigabit Ethernet (1000Base–T) 2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1250 mm (110.1 x 30 x 49.3 in) 2761 x 1840 mm (109 x 72 in) 216 kg (476 lb) 303.5 kg (671.5 lb) Ther, printheads, maintenance cartridge, ink collector, printer stand, spindle, take-up reel, variable front accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) 55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep) 7.4 B(A) (printing); 85 watts (ready); < 2.5 watts (sleep) Input voltage (auto ranging) 200 to 240 VAC (-10% +10%) two wires and PE; 50/60 Hz (+/- 3 Hz); two power cords; 16 A max per power cord EC 60950-1+A1+A2 compliant; USA and Canada (CSA listed EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Australia and New Zealand (RCM) Compliant with Class A requirements, including: USA (FCC
Connectivity Dimensions (w x d x h) Weight What's in the box Environmental ranges Acoustic	Banners, Display Exterior signage, Light boxes – pap Vehicle graphics Interfaces (standard) Printer Shipping Operating area Printer Shipping HP Latex 365 Printer output platen protension kit, loadir reference guide, Operating temperature Operating humidity Sound pressure Sound power Consumption Requirements	s, Double-sided banners, Exhibition and event graphics, Indoor posters, Interior decoration, Light boxes – film, per, Murals, POP/POS, Posters, Textile, Traffic signage, Gigabit Ethernet (1000Base-T) 2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1250 mm (110.1 x 30 x 49.3 in) 2761 x 1840 mm (109 x 72 in) 216 kg (476 lb) 303.5 kg (671.5 lb) nter, printheads, maintenance cartridge, ink collector, printer stand, spindle, take-up reel, variable front ng accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) 55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep) 7.4 B(A) (printing); 85 watts (ready); < 2.5 watts (sleep) Input voltage (auto ranging) 200 to 240 VAC (-10% +10%) two wires and PE; 50/60 Hz (+/- 3 Hz); two power cords; 16 A max per power cord IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Australia and New Zealand (RCM) Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New



Ordering information

Product	V8L39A	HP Latex 365 Printer	
Accessories	F0M56A	HP Latex 64-in Printer 2-in Spindle	
	F0M58A	HP Latex 64-in Printer 3-in Spindle	
	F0M59A	HP Latex 300/500 User Maintenance Kit	
	T7U74A	HP Latex 300/500 Ink Collector	
Original HP printheads	CZ677A	HP 831 Cyan/Black Latex Printhead	
	CZ678A	HP 831 Yellow/Magenta Latex Printhead	
	CZ679A	HP 831 Light Magenta/Light Cyan Latex Printhead	
	CZ680A	HP 831 Latex Optimizer Printhead	
Original HP ink	CZ694A	HP 831C 775-ml Black Latex Ink Cartridge	
cartridges and maintenance	CZ695A	HP 831C 775-ml Cyan Latex Ink Cartridge	
upplies	CZ696A	HP 831C 775-ml Magenta Latex Ink Cartridge	
••	CZ697A	HP 831C 775-ml Yellow Latex Ink Cartridge	
	CZ698A	HP 831C 775-ml Light Cyan Latex Ink Cartridge	
	CZ699A	HP 831C 775-ml Light Magenta Latex Ink Cartridge	
	CZ706A	HP 831 775-ml Latex Optimizer Ink Cartridge	
	CZ681A	HP 831 Latex Maintenance Cartridge	
Original HP large format printing	HP printing materials are designed together with HP Latex Inks and HP Latex printers to provide optimal image quality, consistency, and reliability.		
naterials	HP Permanent Gloss Adhesive Vinyl REACH ¹⁹		
	HP Backlit Polyester Film ♣²0		
	HP PVC-free Durable Smooth Wall Paper REACH,¹9 FSC® certified,²¹ UL GREENGUARD GOLD Certified²²		
	HP Premium Poster Paper ³²⁰ FSC [®] certified ²¹		
	For the entire HP Large Format Printing Materials portfolio, please see <u>HPLFMedia.com</u> .		
Service and support	U9JE3E	HP 2 year Next Business Day with Defective Media Retention HW Support	
	U9JE4E	HP 3 year Next Business Day with Defective Media Retention HW Support	
	U9JE7PE	HP 1 year Post Warranty Next Business Day with Defective Media Retention HW Support	
	U9JE8PE	HP 2 year Post Warranty Next Business Day with Defective Media Retention HW Support	

The color variation inside a printed job has been measured to be within this limit: maximum color difference (95% of colors) <= 2 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard D5 014-6/E:2012. 5% of colors may experience variations above 2 dE2000. Backlit substrates measured in transmission mode may yield different results.



results.

This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.

HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See HPLEMedia.com/hplccosolutions for details.

BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see fsc.org. Not all FSC®-certified products are available in altregions.

UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg or greenguard.org.

or greenguard.org.