

EXPERT// FAMILY The Best Choice for Sign Makers

Expert II 24 Expert II 52 Expert II 24 LX Expert II 52 LX

The Expert Family provides sign makers with optimum speed, superior quality, solid reliability, unmatched value at an affordable price and an eye-catching color combination.



EXPERT//

- 24 in. / 52 in.
- Up to 350 gram of cutting force
- Up to 705 mm / 635 mm (27.8 in. / 25 in.) per second cutting speed (at 45 degree direction)
- · 3 m tracking

EXPERT//LX

- 24 in. / 52 in.
- Up to 350 gram of cutting force
- Up to 705 mm / 635 mm (27.8 in. / 25 in.) per second cutting speed (at 45 degree direction)

Guaranteed 3 meter tracking - grid drum

guarantee 3 meter tracking to ensure quality

outputs and saves you from wasted material

- 3 m tracking
- Advanced contour cutting system AAS II

It comes with a stable drum that can




Advanced AAS II Contour Cutting System

Advanced Automatic-Aligning System (AAS) II) guarantee precise contour cutting by detecting the registration marks on digitally produced images. (Available for Expert II LX models)



reducing the possibility of wasting usable material.





VCM (Patented)

(patented)

and cost.

VCM (Voice Coil Motor) ensure cutting quality. As a result, Expert II can provide sophisticated cutting quality steadily and consistently.



Windows Drivers

Expert II includes a "one click" Windows driver that allows sign makers to edit signs from CorelDraw and Adobe Illustrator output directly to Expert II.



User-friendly interface

It comes with the special VLCD software, providing a simple and intuitive workflow for users of all levels.



Rhinestone Application

Expert II handles rhinetsone stencil cutting with ease, people are amazed with its great versatility.



Dual-port connectivity

GCC Expert II supports dual-port connectivity with USB and serial ports.





Signs Advertisement **Stickers Textile**

Advertisement		Stickers		rextile	
Model Number		EX II-24	EX II-24LX	EX II-52	EX II-52LX
Operational Method		Roller -Type			
Max. Cutting Width		600 mm (23.6 in.)		1320 mm (51.96 in.)	
Max. Cutting Length		50m (164 ft)			
Max. Media Loading Width		719 mm (28.3 in.)		1470 mm (57.87 in.)	
Min. Media Loading Width		50 mm (1.97 in.)			
Number of Pinch Rollers		3			
Acceptable Material Thickness		0.8 mm (0.03 in.)			
Motor Drive		Stepper			
Cutting Force		350 g			
Max. Cutting Speed		Up to 705 mm / sec (27.8 ips) (at 45 degree direction)		Up to 635 mm / sec (25 ips) (at 45 degree direction)	
Acceleration		0.7 G			
Offset		0 ~ 1.0 mm (with an increase of 0.025 mm)			
Mechanical Resolution		0.012 mm (0.00049 in.)			
Software Resolution		0.025 mm (0.00098 in.)			
Distance Accuracy		± 0.254 mm or ± 0.1% of move, whichever is greater			
Repeatability		±0.1mm			
Automatic-Aligning System (AAS II)		Available on Expert II LX models			
Memory Buffer		32 MB /16 MB (when using AAS)			
Interfaces		USB 2.0 (Full speed) & Serial (RS-232C)			
Type of Command		HP-GL, HP-GL / 2			
Control Panel		10 Control Keys and 6 LED			
Diameter of Blade		2.5 mm			
Dimension	(HxWxD) mm	233*8	300 * 255	1065*1632*620	
	(HxWxD) in	9.1*3	34.6*10	41.93 * 62	.25 * 24.41
Net Weight		11 kg	(24.3 lb)	53 kg (116.4 lb)
Stand		Opt	ional	Stan (The dimension and we	dard eight contain the stand)
Power Supply		100-240 VAC, 50 / 60 Hz (auto switching)			
Power Consumption		Max. 288 W			
Environment Temperature		15° C ~ 30° C / 60° F ~ 86° F (operating)			
Environment Humidity		25 % ~ 75 % relative humidity (operating)			

- software to work with Mac OS.)
- ※ The specification and data sheet may vary with different materials used. In order to obtain the best output quality,

 …

 **The specification and data sheet may vary with different materials used. In order to obtain the best output quality,

 **The specification and data sheet may vary with different materials used. In order to obtain the best output quality,

 **The specification and data sheet may vary with different materials used. In order to obtain the best output quality,

 **The specification and data sheet may vary with different materials used. In order to obtain the best output quality,

 **The specification and data sheet may vary with different materials used. In order to obtain the best output quality,

 **The specification are sheet may be sheet
- please maintain the machine regularly and properly. GCC certified material in tracking is Avery MPI 3000.
- * GCC reserves the right to change the specifications without prior notice.
- * The above listed specification values are effective only when operated with media certified by GCC.





GCC Headquarters 4F-1., No.236, Fude 2nd Rd., Xizhi Dist., New Taipei City 22151, Taiwan 886-2-6616-6692 Fax: 886-2-2694-6875 No.1, Chen Feng Road, Yushan, Kunshan, Jiangsu 215300, China 86-512-5726-1515 Fax: 86-512-5726-1518 GCC Europe B.V. Eglantierbaan 43-45, 2908 LV, Capelle a/d IJssel, The Netherlands 31-10-458-9367 Fax: 31-10-451-9874 GCC America, Inc 20453 E Valley Blvd. Walnut, CA 91789, USA

1-909-718-0248 Fax: 1-909-718-0251 US & Canada Only Toll Free: 1-888-284-5211

www.GCCworld.com