

echnical Data Sheet

Issue date: 15/01/2013 Date last modification: 14/12/2016

4-GL3C-08198 HI-GRIP 75 GLOSS WHITE ASP32 EXTRAPERMANENT WKPE135

Face Material

Gloss white polymeric vinyl.

GRAPHICS -

Type Polymeric vinyl Colour and Finish Gloss white

Adhesive

Extra-permanent adhesive with excellent adhesion on low energy surfaces (i.e. PP or PE containers). The adhesive has a very high peel adhesion and medium cohesion.

Reference ASP32

Type Extra permanent

Min. Appl. Temp. +5°C

Service Temp. -40°C/+100°C Shear Medium

Tack 13 N/25mm FINAT FTM9 Final Adhesion 15 N/25mm FINAT FTM2

Liner

Type Siliconised two side PE Kraft

Colour and Finish White

Weight 144 g/m² PP-032 - ISO

±10% 536

Thickness 155 μ ±10% ISO 534 Transparency n.a. % DIN 53 147-64

Applications

Decorative applications for plastics fairing or tanks for motocross, quad bikes and Go Karts; Warning applications on heavy equipment and industrial trucks.

Printing Methods

Printable with UV and solvent screen-printing, UV offset and solvent and eco-solvent based ink-jet.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of $22^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and 50 \pm 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

All information is subject to change without prior notice.





