

ImagePerfect™ 2320 Artistic Fine Art Canvas is a textile which creates the real look and feel of artistic/painting reproductions. It has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks.

IP 2320

ImagePerfect™ 2320 is a canvas textile which allows for the creation of printed output with the real look of artistic paintings. It is especially designed for the presentation of artworks and photos as full colour reproductions, where the structure of the fabric is very pronounced and decorative. Common uses will include reproductions of fine art paintings, textile walls, textile billboards and posters and exhibition panels. It can also be used as a display product fixed in a banner track system. IP 2320 offers a high print quality with remarkable text definition and a large colour gamut to ensure colourful images and vibrant area in-fills. Laminate: ImagePerfect™ water-based liquid laminate with UV protection.

Specifications	
DESCRIPTION	Canvas fabric
COLOUR	White
THICKNESS	520μ
WEIGHT	400g/m ²
TENSILE STRENGTH	N/A
TEAR RESISTENCE	N/A
TEMPERATURE RANGE	N/A
DURABILITY (UNPRINTED)	N/A
FLAME RETARDANCY	N/A
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© August 2015 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use. All technical data are subject to change.

The durability is based on mid European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the graphics. For instance, exterior performance will be decreased in the case of signs facing south, in areas of long high temperature exposure such as southern European countries, in industrially polluted areas or in areas of high altitude. Also, for horizontal applications, exterior performance will decrease.

The print media should be completely dry before further processing, such as cutting, laminating, varnishing or application, or the residual solvents can otherwise change the specific features of the product. To ensure the best possible outcome, the match-component ImagePerfect™ profile should be used with the relevant ImagePerfect™ media.