

ImagePerfect™ 2830-203 is a vinyl laminate with a permanent, solvent-based adhesive system that has been specifically designed for protecting outdoor printed floor graphics.

IP 2830-203

ImagePerfect™ 2830-203 is a textured laminate that provides a non-slip, scuff-resistant surface finish and a high level of transparency. It should be used as a match-component laminate in conjunction with IP 2539 as the print media for outdoor floor graphics. The product has excellent anti-slip properties and resistance to wearing. In order to avoid potential lifting of the product, we would recommend that corners are rounded rather than cut to a sharp 90° angle.

Specifications	
DESCRIPTION	Outdoor floor minder vinyl laminate
COLOUR	Clear matt
THICKNESS	125μ
WEIGHT	N/A
ADHESIVE	Solvent based acrylic, permanent
ADHESIVE STRENGTH	18N / 25mm (Finat TM 1/24h)
RELEASE PAPER	Clay-coated kraft paper, 63g/m²
TEMPERATURE RANGE	-30°C to +90°C
DURABILITY (UNPRINTED)	6 months
FLAME RETARDANCY	N/A
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© September 2015 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use. All technical data are subject to change.

The durability is based on mid European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the graphics. For instance, exterior performance will be decreased in the case of signs facing south, in areas of long high temperature exposure such as southern European countries, in industrially polluted areas or in areas of high altitude. Also, for horizontal applications, exterior performance will decrease.